

Article

Feasibility Study of a Micro Hydro Power Plant for Rural Electrification in Lalumpe Village, North Sulawesi, Indonesia

Meita Rumbayan ^{1,*} and Rilya Rumbayan ²¹ Faculty of Engineering, Sam Ratulangi University, Manado 95115, Indonesia² Department of Civil Engineering, Manado State Polytechnic Polytechnics State of Manado, Manado 95252115, Indonesia; rilya.rumbayan@gmail.com

* Correspondence: meitarumbayan@unsrat.ac.id; Tel.: +62-81241257171

Abstract: This feasibility study aims to assess the potential of implementing a micro hydro system in Lalumpe village, located in North Sulawesi, Indonesia. The study focuses on evaluating the technical and economic aspects of the proposed micro hydro project. Data collection was carried out through field surveys, interviews with local stakeholders, and analysis of available hydrological and topographical data. The technical assessment involved conducting a resource assessment to determine the water availability and potential for harnessing hydroelectric power in the area. The study also examined the village's energy demand and determined the suitable capacity of the micro hydro system required to meet the community's needs. Economic analysis included estimating the initial investment costs, operation and maintenance expenses, and potential revenue generation from the sale of excess electricity to the local grid. Financial viability indicators such as payback period and net present value were calculated to assess the economic feasibility of the project.

Keywords: feasibility study; micro hydro power plant; rural electrification; village in Indonesia

Citation: Rumbayan, M.; Rumbayan,R. Feasibility Study of a Micro Hydro Power Plant for Rural Electrification in Lalumpe Village, North Sulawesi, Indonesia. *Sustainability* **2023**, *15*, x. <https://doi.org/10.3390/xxxxx>

Academic Editor: Adam Smoliński

Received: 28 August 2023

Revised: 17 September 2023

Accepted: 25 September 2023

Published: date



Copyright: © 2023 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

The urgent need to address the challenges of energy access, climate change, and sustainable development has led to increased interest in renewable energy solutions, particularly in remote and rural areas. Micro hydro is one such solution that has gained popularity due to its ability to provide reliable and sustainable electricity from nearby water resources.

This research paper aims to conduct a feasibility study of a proposed micro hydro system in Lalumpe village, located in North Sulawesi, Indonesia. Lalumpe village is a remote community with limited access to electricity and relies mainly on diesel generators for power, which are expensive and environmentally damaging. The novelty of this feasibility study lies in its holistic examination of the micro hydro project, incorporating local insights, technical assessments, community needs, and rigorous financial analyses to present a well-rounded evaluation of the potential implementation in Lalumpe village.

The feasibility study assesses the technical, economic, and environmental aspects of the proposed micro hydro system to determine its viability as a sustainable energy solution for the village. The study considers the available water resources, energy demand, project costs, and revenue generation potential to determine the overall feasibility of the project. The utilization of field surveys, interviews with local stakeholders, and analysis

Comment [M1]: Dear Authors,

(1) Please proofread the article form according to the comments left and pay attention to the highlighted part

(2) Please do not delete the comment during your proofreading, since we need to check point by point after receiving your proofed version. (3) Please just modify or confirm or give

feedback with track change Function

(4) English editing and layout have been complete, please do not revert

the changes. (5) Changing authorship is NOT acceptable during this period

(including adding new

authors/corresponding

authors/affiliations or deleting present

authors/corresponding

authors/affiliations or exchanging

author orders).

Comment [E2]: Please check the change to the title.**Comment [M3]:** Please carefully check the accuracy of names and affiliation

Authorship can not be changed

during this period.

Comment [M4]: We added comma, please confirm.**Comment [M5]:** We added city postcode and country, please confirm**Comment [M6]:** Affiliations only

containing university are not

acceptable. Please carefully confirm

this is an university, if so, please add the

Comment [M7]: Please check all author names carefully.

of hydrological and topographical data reflects a context-specific approach, ensuring that the study is grounded in the local realities and needs of Lalumpe ~~village~~Village.

The paper also discusses the importance of community engagement and participation in the project development process to ensure that the proposed micro hydro system meets the energy needs of the community and aligns with local values and aspirations. It also highlights the regulatory and financing challenges that need to be addressed for the successful deployment of the micro hydro project in the region.

~~The~~This research paper provides valuable insights into the feasibility of implementing a micro hydro system in Lalumpe ~~village~~Village and the potential benefits it can bring to the community. The study serves as a foundation for further project development and decision-making processes, contributing to the development of sustainable energy solutions in remote and rural areas of Indonesia.

The literature review demonstrates that the feasibility study of micro hydro systems in Lalumpe ~~village~~Village aligns with existing research and experiences from various contexts. It emphasizes the importance of assessing technical viability, conducting comprehensive economic analysis, mitigating environmental impacts, and fostering community participation. Drawing on these insights, ~~the~~this study aims to provide a holistic understanding of the feasibility of micro hydro in Lalumpe ~~village~~Village and contribute to sustainable energy development in rural areas of North Sulawesi, Indonesia.

Exploring case studies of similar micro hydro projects can provide valuable insights for the feasibility study in Lalumpe ~~village~~Village. Examples such as the Danau Gerak micro hydro project in Indonesia [1] and the Hindiya micro hydro project in Iraq [2] showcase successful ~~implementation~~implementations and positive socio-economic impacts. These case studies offer practical lessons regarding project management, community engagement, and overcoming challenges.

~~According to~~In [3], the authors conducted ~~the~~a feasibility study of a 320 kW micro hydro power plant project in Cameroon. ~~It~~. ~~They~~ proposed the approach of ~~the~~a feasibility ~~studies by a~~study methodology which can serve as guidance for the other projects ~~offor~~ micro hydro power ~~plant~~ (MHPP)plants (MHPPs) in that country. ~~According to the research in~~. In [4], the authors ~~evaluated~~performed a technical and economic analysis of a ~~Micro Hydropower Plant~~ micro hydro power plant in Cameroon for a ~~Sustainable Development~~ sustainable development. ~~The objective of this work is~~was to ~~do the~~conduct a technical and economic assessment of a MHPP in Bakassa, a remote village in the West Region of Cameroon. They found that this MHPP project can be proposed with installed power of 97 kW, with a ~~9-years~~year payback period.

In [5], a researcher report the work of a ~~Small Hydropower Plants~~small hydropower plant (SHP) at Jaracz ~~is~~which was examined in technical and hydraulic terms. It also ~~analyzes~~analyzed the impact of changes in factors like as water head, flow rate velocity, and trash rack bar shape on predicted SHP profitability. The hydraulic performance evaluation entailed analyzing the effect of a lower flow rate and water head on power output and energy production.

Elbatran et al. ~~examine~~examined the operation, performance, and economics of low head micro-~~hydropower~~ turbines for rural and ~~distant~~remote places. They concluded that low head and micro-~~hydropower~~ are the most secure alternative solutions to the problem of limited electric power supply and financial problems in rural and disadvantaged communities [6].

~~In~~The authors of [7] ~~provides~~provide a comprehensive analysis of the financial and economic aspects of ~~microhydro electricity~~micro hydroelectricity plants in Central Java Province, Indonesia. ~~It~~highlights~~They~~ highlight the potential of utilizing water energy to generate electricity and ~~presents~~present case studies of three different types of ~~microhydro~~micro hydro plants. In [8], micro ~~hydro~~power~~hydropower~~ plants ~~{MHPP} have~~(MHPPs) ~~were~~ proven to be the ~~finest~~best option for electricity generation in remote areas, particularly in areas with dense vegetation and limited economic activity. The

Comment [EE8]: Please check that the intended meaning has been retained.

Comment [EE9]: Please check that the intended meaning has been retained.

Comment [EE10]: Please check that the intended meaning has been retained.

chosen site has the capacity to produce 10 to 20 KW and is located fairly close to Kappadi village, India.

According to [9], small-scale hydro is one of the most cost-effective and environmentally benign energy technologies to be considered for rural electrification in less developed countries. Additionally, it suggests that harnessing the power of falling water through small-scale hydropower plants could provide affordable energy for the development of rural areas. The research discussed in this paper specifically concerns the design and analysis of small-scale hydropower systems to generate electric power from small rivers in Ethiopia, which could be used to energize many off-grid rural areas.

Utilizing low head and micro-hydropower has emerged as a highly reliable alternative to address the challenges posed by insufficient electricity access and financial constraints in underprivileged rural regions. This approach holds the key to fostering a brighter future for the local population. Establishing a strong link between renewable hydropower energy and sustainable development is of utmost importance. Additionally, it is crucial to encourage explorative investigations aimed at advancing the understanding and implementation of this specific scale of power generation [10].

Typically, the generation of an ample power supply demands the construction of a sizable dam, involving substantial capital costs. However, the utilization of low head micro-hydropower installations presents an appealing and efficient approach for generating electricity, particularly in rural, remote, and hilly regions. This is due to the escalating levels of greenhouse gas emissions and fuel prices in such areas, rendering these micro-hydropower systems increasingly favored for deployment along small rivers [11–14].

These micro-hydropower setups have the potential to produce sufficient electrical power to cater to residential, agricultural, and plantation needs, or even for smaller communities. Furthermore, they find application in various mechanical processes, including agro-processing, textile fabrication, cooling, and drying [15]. The primary advantages of low head micro-hydropower systems are their predictability, contingent on a consistent water supply [16], and their favorable environmental impact [17].

According to [18], Indonesia has enormous hydroelectric potential. However, those possibilities are constrained by Indonesia's geography and socioeconomic challenges. The rivers in Indonesia are often unsuitable for the construction of a large-scale hydroelectric facility. Although hydropower plants are required to provide renewable energy base loads, the usage of hydropower can be enhanced in a variety of ways. One option is to reduce the hydropower plant's capacity and build micro-hydropower plants. Micro-hydropower plants will be an important addition to rural communities and agricultural areas as generators of community-based energy.

The range of total plant cost of MHP projects in Nepal and Pakistan was more than USD 2000 per kW during 2000 [19]. The cost per kW for MHP projects for electricity supply including transmission implemented in Sri Lanka, Nepal, Peru, and Zimbabwe was found to be in the range of USD 1136–5630 [20]. The cost for the MHP projects in India for decentralized power supply for villages situated in remote and inaccessible areas is estimated to be in the range of USD 2670–5010 per kW [21]. In this study, an investment cost of USD 2000 per kW is used for planning to build a micro-hydropower plant in Tulaun River, including equipment cost, construction cost, and installation. For operation and maintenance, about 2% of the investment cost is chosen as the annual cost to be considered in the calculation for the financial analysis.

This article is structured as follows: the introduction is provided in Section 1, the materials and methods in Section 2, the results in Section 3, and the discussion in Section 4, as well as the conclusion in Section 5.

2. Materials and Methods

The methodology outlined below ensures a systematic and comprehensive approach to assessing the feasibility of a micro hydro system in Lalumpe ~~village~~Village, North Sulawesi, Indonesia. By combining data collection, technical analysis, and economic evaluation ~~the, this~~ study aims to provide valuable insights and recommendations for the successful implementation of a sustainable and community-driven micro hydro project in North Sulawesi, Indonesia.

1. Study Area Selection: The first step in the methodology is to select Lalumpe ~~village~~Village as the study area. Considerations such as the village's energy needs, geographical location, water resources availability, and accessibility are taken into account. Collaboration with local authorities and community leaders is established to ensure their support and participation in the study.
2. Data Collection: ~~Data~~The data collection involves gathering relevant information to assess the feasibility of a micro hydro system in Lalumpe ~~village~~Village. The following data sources and methods are utilized:
 - a. Resource Assessment: Conduct a field survey to measure stream flow rates, head, and other hydrological parameters. Gather topographical data through satellite imagery and land surveys to identify potential micro hydro sites.
 - b. Energy Demand Assessment: Conduct surveys and interviews with community members to determine the energy needs of Lalumpe ~~village~~Village. Collect data on current energy sources, consumption patterns, and load requirements.
 - c. Financial Data: Collect data on project costs, including equipment, construction, installation, and operation and maintenance expenses. Explore funding options, grants, and financial incentives available for renewable energy projects.
3. Technical Design: Based on the resource assessment data, develop a technical design for the micro hydro system. Determine the appropriate turbine type, capacity, and distribution infrastructure required to meet the energy demand of Lalumpe ~~village~~Village. Consider the specific characteristics of the water resources and topography identified in the resource assessment.
4. Economic Analysis: Perform an economic analysis to evaluate the financial feasibility of the micro hydro project. Calculate the initial investment costs, including equipment, construction, and installation expenses. Estimate the operation and maintenance costs and assess the potential revenue generation from electricity sales or other income streams. Apply financial indicators such as net present value (NPV), internal rate of return (IRR), and payback period (PB) to assess the economic viability of the project.
5. Discussion and Recommendations: Compile the findings of the feasibility study into a comprehensive report with the technical and economic assessments. Provide clear recommendations on the viability of the micro hydro project in Lalumpe ~~village~~Village, including potential funding sources, implementation strategies, and future ~~plan~~planned works for implementation.

3. Results

3.1. Study Area Selection

Lalumpe ~~village~~Village is the location of the case study which is located at ~~latitude~~ 05°33'20.8" ~~North Latitude~~ ~~north latitude~~ and 127°09'6.8" ~~East Longitude~~ ~~east longitude~~. Because the area is quite remote, this location often experiences power outages. Nonetheless, the area has many renewable local resources, such as two rivers, namely the Tulaun River and the Kawis River. Thus, a renewable energy-based micro-grid system ~~is a prospect for realizing~~has the potential to realize an energy-independent village. This study proposes micro ~~hydro power~~hydropower systems to power a small sub-village inhabited by 55 households ~~with potency of using the~~ micro hydro ~~resource~~resources that ~~are~~ located in the village. The ~~locus of research~~study site of Lalumpe ~~village that~~ Village.

Comment [EE11]: Please check that the intended meaning has been retained.

which is located in the Minahasa regency of North Sulawesi, Indonesia, is shown in Figure 1.



Figure 1. The location of Lalumpe village as the study area selection of Lalumpe Village.

The energy demand assessment for the village was conducted based on surveys and interviews with the village community to determine the energy needs of the community. The typical load requirement of the community is described as the daily profile pattern shown in Figure 2.




Figure 2. The daily profile of community's load requirement.

3.2. Technical Assessment

3.2.1. Resource Assessment

For the resource assessment, we conducted a detailed assessment of the available water resources in Lalumpe village to determine the potential for micro hydro power generation. This assessment includes:

- Hydrological Data Collection: The stream flow rates, water levels, and other hydrological parameters were measured at various points within the potential micro hydro sites. The flow of water in a natural river is typically measured in cubic meters per second (cms) or cubic feet per second (cfs). Weirs and flumes are structures installed in a river to create a specific flow constriction. By measuring the water level upstream or downstream of the weir or flume, and knowing the geometry of the structure, the flow rate can be calculated. The result of the stream flow measurement is presented in Table 1.
- Topographical Survey: A topographical survey of the selected micro hydro sites was conducted using land surveying equipment. The elevation differences (head) between the intake and turbine locations was identified to de-

Comment [EE12]: Please check that the intended meaning has been retained.

termine the available energy potential. [The result of ~~potency head~~ these measurement of the river head is presented in Table 1.]

The [images taken during the data collection and topographical survey in the micro hydro site (Tulaun ~~river~~ thatRiver) located in Lalumpe ~~village~~Village] are shown in Figure 3.



Figure 3. The data collection and topographical survey in the micro hydro site: (Tulaun ~~river~~ thatRiver) located in Lalumpe ~~village~~Village [23].

The formula to calculate the The micro hydro potential (P) of a site is determined by using the following equation:

$$P = \rho \cdot g \cdot Q \cdot H \cdot \eta \quad (1)$$

where P is the power output in watts (W) or kilowatts (kW), ρ is the density of water (typically around 1000 kg/m³), g is the acceleration due to gravity (approximately 9.81 m/s²), Q is the flow rate of water in cubic meters per second (m³/s), H is the head or vertical drop in meters (m), and η is the overall efficiency of the micro hydro system (expressed as a decimal). This formula represents the theoretical maximum power that can be extracted from a hydroelectric system under ideal conditions. ~~It's~~It is important to note that actual performance may be lower due to factors like losses in the system (e.g., friction, inefficiencies in turbines and generators). Real-world performance is typically expressed as a percentage of the theoretical potential.

Based on the ~~resources~~resource assessment, the potential for water resources in the Tulaun River is outlined in Table 1.

Table 1. The ~~potency of~~ resource assessment ~~on of~~ micro hydro site.

Potency Parameter	Low	Medium	High
Waterflow rate {(m³/s)}	0.5	0.6	0.7
Head {(m)}	3	4	5
Efisiensi Efficiency	0.85	0.85	0.85
Power {(kW)}	12.5	20	29.2

Due to the unavailability of yearly rainfall data at the location, the rainfall information was obtained through interviews with the local community, who stated that the river does not experience a dry season.

3.2.2. System Design

Based on the resource assessment, ~~design the~~ micro hydro system ~~was designed~~ to meet the energy demand of Lalumpe ~~village~~. ~~Consider the Village. The~~ following aspects ~~were considered~~:

Comment [EE13]: Please check that the intended meaning has been retained.

Comment [EE14]: Please check that the intended meaning has been retained.

Comment [M15]: Please ensure that permission has been obtained and there is no copyright issue. If copyright is needed, please provide citation in the following format: "Reprinted/adapted with permission from Ref. [XX]. Copyright year, copyright owner's name". More details on "Copyright and Licensing" are available via the following link: <https://www.mdpi.com/ethics#10>.

Comment [M16]: Please keep the format unified in the manuscript and equations and change the font accordingly (italics/regular font). Please check all variables in the full text and unify the format

Comment [EE17]: Please check that the intended meaning has been retained.

Comment [EE18]: Please check that the intended meaning has been retained.

- a. Turbine Selection: Select an appropriate turbine type was selected based on the available head and flow rate. ConsiderThe considered factors such aswere efficiency, maintenance requirements, and cost-effectiveness. CommonThe common turbine types for micro hydro systems include Pelton, Francis, and Cross-Flowcross flow turbines, as shown in Figure 4.




Figure 4. The range of selection of small and micro hydro turbines with headshead and flow ratesrate variations [10].

Figure 4 presents the categorization of various small hydropower plants based on factors such as head height, discharge (flow rate), and capacity. Large run-of-the-river plants, which employ Impellerimpeller turbines, are characterized by high flow rates and low head heights. Conversely, mountain-based dam installations, driven by Pelton turbines, are characterized by a low discharge and high head. Plants with intermediate flow rates and head heights typically utilize Francis turbines.

- b. System Capacity: Determine theThe required capacity of the micro hydro system to meet the energy needs of Lalumpe village. Consider theVillage was determined. The village's current and future energy demand, seasonal variations, and load requirements were considered.

3.2.3. Equipment Selection

In equipmentthe selection of equipment, we selectselected the necessary equipment for the micro hydro system based on the design specifications and local conditions:

- a. Intake Structure: Design and select anAn intake structure that allows for proper water diversion, as shown in Figure 45, and design of power house, as shown in Figure 56, were designed.

Comment [M19]: Please use periods as decimal signs instead of commas, e.g., "0,1" should be "0.1".

Comment [M20]: Please ensure that permission has been obtained and there is no copyright issue. If copyright is needed, please provide citation in the following format: "Reprinted/adapted with permission from Ref. [XX]. Copyright year, copyright owner's name". More details on "Copyright and Licensing" are available via the following link: <https://www.mdpi.com/ethics#10>.

Answer:

We decide to delete Figure 4 as we cannot ensure to obtain the permission about the Figure 4.

Comment [EE21]: Please check that the intended meaning has been retained.




Figure 56. Layout of power house of micro hydro system in Tulaun ~~river~~River at Lalumpe Village.

- b. Penstock: ~~Determine the~~The optimal diameter and material for the penstock ~~were determine~~, considering the head, flow rate, and distance between the intake and turbine, as shown in Figure 67.





Figure 67. The components of civil work ~~of~~for micro hydro ~~plant~~ in Tulaun ~~river~~River.

- c. Turbine and Generator: ~~Choose a~~A turbine and generator combination ~~was selected~~ that ~~match~~matched the specific site conditions and system requirements.

Formatted

The selection of an MHP turbine and generator specifications ~~is was~~ based on the needs, design, budget, and market availability of MHP equipment. ~~The example of a PLTMH turbine and generator is shown in Figure 8.~~



~~Figure 8. Example of an MHP turbine and generator [23].~~

The expected performance of the micro hydro system based on the design parameters by using the available head and flow rate data ~~can be considered as an~~ independent power supply of 12.5 kW to ~~generate/fulfill the~~ village's energy demand ~~is described as describe in the~~ profile load in (Figure 2.).

3.3. Economical ~~Assessment/Assessment~~

3.3.1. Cost Estimation

~~Estimate~~We estimated the capital costs associated with the micro hydro system which included the following:

- Equipment Costs: ~~Calculate the~~The costs of turbines, generators, penstocks, intakes, transmission lines, and other necessary equipment based on market prices and project-specific requirements.
- Construction Costs: ~~Estimate the~~The costs of civil works, such as excavation, concrete structures, and installation of equipment. ~~Consider~~ considering the site conditions and accessibility when assessing the construction costs.
- Miscellaneous Costs: ~~Estimate the~~The ongoing costs associated with operating and maintaining the micro hydro system.

The cost estimation of an MHPP depends on the site ~~to where it will~~ be installed. The following table, Table 2, shows the cost estimation for a micro hydro plant in Lalumpe village/Village with ~~thea~~ budget ~~to be proposed of~~ about USD 2000 US\$ per kW or ~~all the~~ total project ~~planning~~cost, based on the literature review in [20–22].

Table 2. Power generating, investment cost, energy generation, and electricity sales in a year of micro hydro system ~~operation~~.

Power Generating Generation (kW)	Investment Cost (US\$)USD)	Energy Generating Generation (kWh/Year)	Electricity Sales (US\$)USD)
12.5	25,000	76,650	7665
20	40,000	122,640	12,264
29	58,000	179,054	17,905.4

3.3.2. Revenue Generation

~~Assess~~We assessed the potential revenue generation opportunities associated with the micro hydro system using the following:

Comment [M25]: 1. please check 2.400,00 if should be 240,000, or 2.400.00, please check which one is correct and revise all.

2. Please change hyphen to en dash.
3. Please removed watermark.

Answer:

We decide to remove the Figure 8. It no need to use in the manuscript

Comment [M26]: Please ensure that permission has been obtained and there is no copyright issue. If copyright is needed, please provide citation in the following format:

Comment [EE27]: Please check that the intended meaning has been retained.

Comment [EE28]: Please check that the intended meaning has been retained.

Comment [M29]: We moved here, after its first citation. Please confirm

Comment [EE30]: Please check that the intended meaning has been retained.

Comment [M31]: We revised this to normal paragraph, please confirm. Same as below.

- a. Electricity Sales: ~~Estimate~~ the revenue that can be generated by selling the excess electricity generated by the micro hydro system to the local grid or nearby communities ~~was estimated~~.
- b. Off-Grid Applications: ~~Identify potential~~ **Potential** revenue streams from off-grid applications ~~were identified~~, such as providing electricity to local businesses, community facilities, or agricultural operations. ~~Assess the~~ **The** market demand and potential income from these sources ~~were assessed~~.

The economic analysis was carried out to evaluate the potential revenue of operating an micro hydro plant in Tulaun ~~river~~ **River** to supply ~~off-grid~~ electricity ~~off-grid~~ to local communities ~~in~~ **outside the** village. ~~With a~~ comparison ~~to was performed between the~~ electricity ~~salessale~~ costs of Rp. IDR 1400 per kWh (0.1 ~~US\$USD~~ per kWh) ~~with and the~~ electricity price ~~by of the~~ national grid. In this study, ~~it is counted~~ **the operation time was set to** 8760 h (a year) and taking into account the PF power factor of 70%, the ~~potency-~~ **potential** electricity sales by ~~the~~ micro hydro system that will be obtained in one year is given in Table 2.

3.3.3. Financial Analysis

~~Conduct a~~ **A** financial analysis ~~was conducted~~ to determine the economic viability of the micro hydro project. ~~Calculating financial~~ **Financial** indicators such as NPV, IRR, and Payback Period ~~is typically done~~ **were calculated** using formulas in Excel or financial ~~calculators/~~ **software**.

- a. Net Present Value (NPV): The Net Present Value represents the difference between the present value of cash inflows and outflows over a specified time period. ~~Calculate the~~ **The** NPV ~~was calculated~~ by discounting the projected cash flows over the project's lifespan to their present value. ~~Consider the~~ **The** appropriate discount rate that reflects the project's risks and opportunity costs: ~~was considered~~. The discount rate can be found using the interest rate; ~~in this study,~~ it ~~is was~~ assumed that the interest rate is 10% (based on the data in 2020 at <https://www.statista.com/statistics/794458/indonesia-real-interest-rates/> accessed on 27 August 2023). The ~~calculation of~~ **Net present value** **Present Value** can be ~~obtained by~~ **calculated** using the following equation:

$$NPV = \sum_{t=0}^n \frac{CF_t}{(1+r)^t} \quad (2)$$

where NPV is the ~~net present value~~ **Net Present Value**, CF_t is the cash flow in ~~that~~ period, r is the discount rate %, n is the lifetime of the project (year), and $(1/1+r)^t$ ~~is the~~ discount rate which represents the NPVs for different discount rates. The ~~calculation of~~ **calculated** **Net present value is** **Present Values are** shown in Table 3.

Table 3. ~~The Calculation of~~ Net Present Value for a capacity of 12.5 kW.

Year	Discount Factors Factor	Cash Flow (US\$ USD)	Present Value (US\$ USD)
0	1	-25,000	-25,000
1	0.91	7165	6513.64
2	0.83	7165	5921.49
3	0.75	7165	5383.17
4	0.68	7165	4893.79
5	0.62	7165	4448.90
6	0.56	7165	4044.46
7	0.51	7165	3676.78
8	0.47	7165	3342.53
9	0.42	7165	3038.66

Comment [EE32]: Please check that the intended meaning has been retained.

Comment [EE33]: Please check that the intended meaning has been retained.

Comment [EE34]: Please check that the intended meaning has been retained.

Comment [M35]: Please state the version number of the software.
Answer: We remove/delete the word of software in the manuscript.

Comment [M36]: We added access date, please confirm.
Answer: Ok

Comment [M37]: Please check if lac content in box
Answer: There is no content. Please delete the box.

$$NPV = \sum_{t=0}^n \frac{CF_t}{(1+r)^t}$$

10	0.39	7165	2762.42
NPV			19,025.82

From the results of these calculations it is ~~known~~shown that the NPV value for 10th year ~~obtained~~ is US\$USD 19,025.82. This indicates that the NPV > 0 which means ~~that~~ the project is feasible to continue.

b. Internal Rate of Return (IRR)

The Internal Rate of Return (IRR) is the discount rate that makes the Net Present Value of a series of cash flows equal to zero. In other words, ~~it's~~it is the rate at which the present value of inflows equals the present value of outflows.

The formula to calculate the IRR is presented in Equation (3).

$$0 = \sum_{t=0}^n \frac{CF_t}{(1+IRR)^t} \quad (3)$$

where CF_t is the ~~Cash~~cash flow in ~~that~~ period and n is the total number of periods.

From the results of these calculations, it is ~~known~~shown that the IRR value ~~is~~ 26% for ~~a micro hydropower plant with a capacity of~~ 12.5 kW, 27% for ~~a plant with a capacity of~~ 20 kW, and 25% for ~~a capacity of~~ 30 kW ~~of micro hydro power plant~~.

c. ~~Payback Period~~The ~~payback period~~ is ~~defines~~defined as the ~~assessment of the~~time required for the project to recover its initial costs. In this study, the calculation of ~~the~~ payback period is equal to ~~the~~ initial investment for ~~the~~ project ~~divide to divided by~~ ~~the~~ cash flow per year.

The result of ~~the~~ payback period ~~calculation~~calculations for each ~~planning~~planned capacity ~~offor the~~ micro ~~hydro power~~hydropower plant ~~have been~~are shown in Table 4. Based on the calculation results, the ~~the~~ payback period for ~~the~~ investment ~~can occur for~~ ~~was~~ 3.5 years, 3.4 years ~~and, or~~ 3.6 years for ~~the~~ three ~~planning~~scenarios ~~offor a~~ micro ~~hydro power~~hydropower plant ~~in the~~at this site.

Using the same method, the ~~net present values~~Net Present Values, Internal Rate Return (IRR), and ~~Payback Period~~payback period for the micro ~~hydro power~~hydropower plant capacities of both 20 kW and 29 kW have been calculated and are reported in Table 4.

Table 4. The comparison of Net Present Value, ~~IRR~~, and ~~IRR and Payback Period~~payback period.

Years Parameter	MHPP Capacity of 12.5 kW	MHPP Capacity of 20 kW	MHPP Capacity of 29 kW
Initial investment (US\$)USD	-25,000	-40,000	-58,000
Cash flow per year (US\$)USD	7165	11,764	16,705
NPV (US\$)USD	\$19,025.82	\$32,284.69	\$42,644.99
IRR	26%	27%	25%
Payback Period period (years)	3.5	3.4	3.6

These formulas are widely used in finance to assess the feasibility and profitability of investments. It is imperative to note that a positive Net Present Value (NPV) and a superior Internal Rate of Return (IRR) generally signify a more favorable investment proposition.

4. Discussion

The findings of this feasibility study indicate that Lalumpe ~~village~~Village has favorable conditions for the implementation of a micro hydro system. The analysis sug-

Comment [M38]: Please check if lack content in box.

Answer: Please remove the box

~~the IRR is presented in Equa~~

$$0 = \sum_{t=0}^n \frac{CF_t}{(1+IRR)^t}$$

~~that period and n is the total~~

Comment [EE39]: Please check that the intended meaning has been retained.

gests that the project has the potential to provide a reliable and sustainable source of electricity to meet the energy needs of the community while contributing to reduced greenhouse gas emissions and dependence on fossil fuels.

However, challenges related to financing, community engagement, and regulatory aspects were also identified during the study. These challenges should be addressed through strategic partnerships, community involvement, and adherence to local regulations to ensure the successful implementation of the micro hydro project.

Overall, the feasibility study demonstrates the potential benefits of implementing a micro hydro system in Lalumpe ~~village~~Village, providing insights ~~intothrough~~ the technical and ~~economics asesment~~. ~~Theeconomic assessments~~. This study serves as a valuable foundation for further project development, stakeholder engagement, and decision-making processes regarding the deployment of sustainable energy solutions in the region.

In accordance with the Indonesian National Energy Policy, renewable energy will make up 31% of the country's energy mix by 2050. This will be made up of 23% biomass, 21% biodiesel, 20% geothermal, 10% hydropower, 7% nuclear, 6% coal gas methane, 4% bioethanol, and the remaining 8% ~~consisting~~ of biogas, solar, wind, and marine sources [24].

Overall, the feasibility of a micro ~~hydro-power~~hydropower plant depends on a combination of technical, economic, and environmental factors. A thorough feasibility study is necessary to determine whether a micro ~~hydro-power~~hydropower plant is a viable option for a particular location. By evaluating these factors, a feasibility study provides a comprehensive analysis of the costs and benefits of a micro ~~hydro-power~~hydro-power plant project. This helps stakeholders make informed decisions regarding the viability and potential benefits of such projects. Future research should focus on integrating emerging technologies and sustainable practices to enhance the feasibility assessment process for micro ~~hydro-power~~hydropower projects.

When considering small hydropower facilities, the expenses associated with investments can be categorized into two segments. The initial element encompasses the expenses linked to ~~the~~ electromechanical equipment, which, according to the findings of scholarly research, can be reasonably approximated. Generally, for newly established small hydropower plants, the ~~outlaycosts~~ for electromechanical equipment constitutes approximately 30–40% of the overall investment. This aspect also takes precedence when it comes to the refurbishment of existing small hydropower plants. The second element of the investment budget allocated for small hydropower plants encompasses additional expenditures related to land acquisition, infrastructure costs, and labor expenses. Estimating these additional costs is notably challenging due to their strong reliance on local circumstances. Factors such as the location of the hydropower installations, specifically potential challenges related to accessing the intended site, and the associated local prices of construction materials, significantly influence these costs [235–2830].

Community-based micro hydro is a promising technology for providing sustainable energy to rural communities. It has the potential to provide reliable, clean energy while promoting local economic development and improving the quality of life for rural communities. However, successful implementation requires active community participation, effective management and governance, and access to technical and financial resources. Further research and investment in this area could help to overcome these challenges and expand the use of community-based micro hydro as a sustainable energy solution. Community-based micro hydro is a sustainable energy solution that has gained popularity in rural areas where grid electricity is not available or is unreliable. This technology involves harnessing the power of flowing water in a small stream or river to generate electricity that can be used to power homes, businesses, and community facilities. Community-based micro hydro systems are typically designed, constructed, and managed by local communities, and are therefore well-suited to address the energy needs of rural communities.

Comment [EE40]: Please check that the intended meaning has been retained.

Furthermore, ~~analyze~~ the ~~analysis of~~ potential social and cultural impacts of the micro hydro project can be future work ~~involve as follows which involves the following~~:

- Community Engagement: ~~Engage~~~~Engaging~~ with the local community and stakeholders to understand their perspectives, concerns, and aspirations related to the project. ~~Incorporate~~~~Incorporating~~ their input into the project design and decision-making processes.
- Cultural Heritage: ~~Identify~~~~Identifying~~ and ~~assess~~~~assessing~~ any potential impacts on cultural heritage sites or traditions in the project area. ~~Develop~~~~Developing~~ mitigation measures to protect and preserve cultural assets, if applicable.
- Social Benefits: ~~Identify~~~~Identifying~~ the potential positive impacts of the micro hydro project on the local community, such as increased access to electricity, improved livelihoods, and enhanced educational opportunities.

~~It is a challenge to~~To develop micro hydro ~~system by exploring~~systems, we must ~~explore~~ the potential financing options for ~~the~~ micro hydro project ~~with 3~~through three options ~~strategies~~. ~~Firstly, Subsidies:~~ ~~subsidies~~ or financial incentives available for renewable energy projects in the region. ~~Secondly, research;~~ financial institutions that provide loans or financing specifically for renewable energy projects. ~~Thirdly; and~~ the possibility of community-based financing models, such as crowd funding or community investment, ~~to raise funds for the micro hydro project~~.

5. Conclusions

The technical and economic aspects of the proposed micro ~~hydro power~~hydropower plant, including ~~resource assessment~~assessments of resources, energy demand, investment costs, and revenue generation have been presented in this feasibility study. By conducting a comprehensive feasibility study of a micro hydro system in Lalumpe ~~village~~Village, this research paper intends to provide valuable insights into the potential for sustainable energy development in rural areas of Indonesia. The findings will contribute to evidence-based decision-making, encourage renewable energy adoption, and support the development of inclusive and sustainable energy systems in remote communities.

Overall, this study underscores the potential benefits of implementing a micro hydro system in Lalumpe ~~village~~Village, presenting a holistic evaluation that considers both the technical and economic aspects. However, it is imperative to note that ongoing monitoring and periodic reassessment will be essential to ensure the sustained success and long-term viability of the proposed project.

Author Contributions: Conceptualization, M.R. and R.R.; methodology, M.R.; validation, M.R. and R.R.; formal analysis, R.R.; investigation, M.R.; resources, M.R.; data curation, R.R.; writing—original draft preparation, M.R.; writing—review and editing, R.R.; visualization, R.R.; project administration, R.R.; funding acquisition, M.R. All authors have read and agreed to the published version of the manuscript.

Funding: The authors would like to thank the Ministry of Education, Culture, Research and Technology Education of Indonesia for the funding through ~~the~~ Directorate Research, Technology and Community Service.

Institutional Review Board Statement:

Informed Consent Statement:

Data Availability Statement:

Conflicts of Interest: The authors declare no conflict of interest.

References

- Ulya, N.A.; Waluyo, E.A.; Kurnarso, A. Analisis Ekonomi Pengembangan Pembangkit Listrik Tenaga Hidro: Studi Kasus di Kabupaten Muara Enim, Sumatera Selatan. *J. Anal. Kebijak. Kehutan*. **2019**, *16*, 31–45.

Comment [EE41]: Please check that the intended meaning has been retained.

Comment [M42]: We moved Acknowledgments Section to the Funding Section, please confirm.
Answer: Please add the acknowledgment that the Author acknowledge support by Ministry of Education, Culture, Research and Technology Education of Indonesia for the funding through the Directorate Research, Technology and Community Service, Sam Ratulangi University and Manado State Polytechnics.

Comment [M43]: If there is not involving humans or animals, please write "Not applicable".
Answer: Not applicable

Comment [M44]: If there is not involving humans or animals, please write "Not applicable".
Answer: Not applicable

Comment [M45]: If there is nothing, please write "Not applicable".

We encourage all authors of articles published in MDPI journals to share

Comment [M46]: We changed it to a standard note. Please confirm this revision.

Comment [M47]: Please do not change the reference format with EndNote and other tools. Our production editor has done thoroughly layout work for the

2. Alshami, A.H.; Hussein, H.A. Feasibility analysis of mini hydropower and thermal power plants at Hindiya barrage in Iraq. *Ain Shams Eng. J.* **2021**, *12*, 1513–1521. <https://doi.org/10.1016/j.asej.2020.08.034>.
3. Signe, E.B.K.; Hamandjoda, O.; Nganhou, J. Methodology of Feasibility Studies of Micro-Hydro Power Plants in Cameroon: Case of the Micro-Hydro of KEMKEN. *Energy Procedia* **2017**, *119*, 17–28. <https://doi.org/10.1016/j.egypro.2017.07.042>.
4. Elie Bertrand, K.; Hamandjoda, O.; Nganhou, J.; Wegang, L. Technical and Economic Feasibility Studies of a Micro Hydro-power Plant in Cameroon for a Sustainable Development. *J. Power Energy Eng.* **2017**, *5*, 64–73. <https://doi.org/10.4236/jpee.2017.59006>.
5. Walczak, N. Operational Evaluation of a Small Hydropower Plant in the Context of Sustainable Development. *Water* **2018**, *10*, 1114. <https://doi.org/10.3390/w10091114>.
6. Elbatran, A.H.; Yaakob, O.B.; Ahmed, Y.M.; Shabara, H.M. Operation, performance and economic analysis of low head micro-hydropower turbines for rural and remote areas: A review. *Renew. Sustain. Energy Rev.* **2015**, *43*, 40–50. <https://doi.org/10.1016/j.rser.2014.11.045>.
7. Purwanto, Financial and Economic Analysis of Microhydro Electricity Plants, at Some Locations, Central Java Province, Indonesia. *J. Penelit. Sos. Ekon. Kehutan.* **2011**, *8*, 251–264. (In Indonesian)
8. Palakshappa, K.; Rudresha, N.; Kumar, V. Feasibility study on proposed micro hydro power plant Kappadi (Byndoor), Karnataka, India. In Proceedings of the International Conference on Industrial Engineering and Operations Management, Bangkok, Thailand, 5–7 March 2019.
9. Dametew, A.W. Design and Analysis of Small Hydro Power for Rural Electrification. *Glob. J. Res. Eng.* **2016**, *16*, 25–45.
10. Elbatran, A.H.; Yaakob, O.B.; Ahmed, Y.M.; Shabara, H.M. Operation, performance and economic analysis of low head micro hydro power turbines for rural and remote areas: A review. *Renew. Sustain. Energy Rev.* **2015**, *43*, 40–50.
- 11–10. Ghosh Tushar, K.; Prelas Mark, A. *Energy Resources and Systems. Renewable Resources*; Springer: Dordrecht, The Netherlands, 2011; Chapter 3.
- 12–11. Derakhshan, S.; Nourbakhsh, A. Experimental study of characteristic curves of centrifugal pumps working as turbines in different specific speeds. *Exp. Therm. Fluid Sci.* **2008**, *32*, 800–807.
- 13–12. Banos, R.; Manzano-Agugliaro, F.; Montoya, F.G.; Gil, C.; Alcaide, A.; Gómez, J. Optimization applied to renewable and sustainable energy: A review. *Renew. Sustain. Energy Rev.* **2011**, *15*, 1753–1766.
- 14–13. Paish, O. Micro-hydropower: Status and prospects. *Proc. Inst. Mech. Eng. Part A J. Power Energy* **2002**, *216*, 31.
- 15–14. Prodanovic, M.; Miltenović, A.; Nikodjević, M. Determination of operating parameters of turbines for micro hydroelectric power plants for optimal use of hydropower. *IOP Conf. Ser. Mater. Sci. Eng.* **2019**, *659*, 012046.
- 16–15. Singh, D. *Microhydro Power Resource Assessment Handbook*; Prepared for APCIT Asian and Pacific Centre for Transfer of Technology of the United Nations; Economic and Social Commission for Asia and the Pacific (ESCAP): Bangkok, Thailand, 2009.
- 17–16. Teuteberg, B.H. *Design of a Pump-As-Turbine for an Abalone Farm*; Final Report for Mechanical Project 878; Department of Mechanical and Mechatronic Engineering, Stellenbosch University: Stellenbosch, South Africa, 2010.
- 18–17. Yaakob, O.B.; Ahmed, Y.M.; Elbatran, A.H.; Shabara, H.M. Are view on micro hydro gravitation alvortex power and turbine systems. *J. Teknol. (Sci. Eng.)* **2014**, *69*, 1–7.
- 19–18. Ardiansyah, H. *Hydropower Technology: Potential, Challenges, and the Future*; BRIN Publishing: Jakarta, Indonesia, 2022. Available online: <https://penerbit.brin.go.id/press/catalog/download/562/475/11489?inline=1> (accessed on 27 August 2023).
- 20–19. Rijal, K. *Mini and Micro Hydro Power Development: Status, Issues and Strategies for the Hindu Kush Himalayan Region, Vol. 9*. Publication of NESS. *A J. Eng. Inst. Eng. Kathmandu Nepal* **2000**; Abid Hussain, Gopal K. Sarangi, Anju Pandit, Sultan Ishaq, Nabir Mamnun, Bashir Ahmad, Muhammad Khalid Jamil. *Hydropower development in the Hindu Kush Himalayan region: Issues, policies and opportunities, Renewable and Sustainable Energy Reviews, Volume 107, 2019, Pages 446-461, ISSN 1364-0321, https://doi.org/10.1016/j.rser.2019.03.010*.
- 21–20. Khennas, S.; Barnett, A. *Best Practices for Sustainable Development of Micro Hydro Power in Developing Countries*; The Department for International Development: London, UK; The World Bank: Washington, DC, USA, 2000.
- 22–21. Nouni, M.R.; Mullaik, S.C.; Kandpal, T.C. Techno-economics of micro-hydro projects for decentralized power supply in India. *Energy Policy* **2006**, *34*, 1161–1174. <https://doi.org/10.1016/j.enpol.2004.10.016>.
23. Meita Rumbayan, S.T.; Rilya Rumbayan, S.T.; Christy Pasiowan, S.T.; Manahampi, F. *Perencanaan Pembangkit Listrik Tenaga Mikro Hidro (Studi Kasus di Sungai Tuluan Desa Lalumpe Minahasa)*; Ahlimedia Manado: Kota Malang, Indonesia, 2022.
- 24–22. Barelli, L.; Liucci, L.; Ottaviano, A.; Valigi, D. Mini hydro: A design approach in case of torrential rivers. *Energy* **2013**, *58*, 695–706.
- 25–23. Singal, S.K.; Saini, R.P. Analytical approach for development of correlations for cost of canal-based SHP schemes. *Renew. Energy* **2008**, *33*, 2549–2558.
- 26–24. Ogayar, B.; Vidal, P.G. Cost determination of the electro-mechanical equipment of a small hydro-power plant. *Renew. Energy* **2009**, *34*, 6–13.
- 27–25. Aggidis, G.A.; Luchinskaya, E.; Rothschild, R.; Howard, D.C. The costs of small-scale hydro power production: Impact on the development of existing potential. *Renew. Energy* **2010**, *35*, 2632–2638.
- 28–26. Mishra, S.; Singal, S.K.; Khatod, D.K. Optimal installation of small hydropower plant—A review. *Renew. Sustain. Energy Rev.* **2011**, *15*, 3862–3869.

Comment [M48]: We removed "ISSN" please confirm all.

Comment [M49]: Refs. 6 and 10 are duplicated. Please confirm if Ref. 10 can be removed. If so, we will help to remove it and rearrange the Ref. citations accordingly. If not, please replace Ref. 10 with another related reference which is different from anyone of other references.

Answer: Please remove Ref 10 and Ref 23

Comment [M50]: Please provide the correct author names. There should be the name abbreviation after surname.

Comment [M51]: We removed "IEO Society International", please confirm.

Comment [M52]: We removed "Version 1.0. Global Journals Inc. (USA)", please confirm.

Comment [M53]: We added journal pagination, please confirm.

Comment [M54]: We added city name, please confirm.

Comment [M55]: Please check if the page is correct.

Comment [M56]: We added the publisher's location. Please confirm.

Comment [M57]: We added the name of the publisher, location and year.

Comment [M58]: We added access date, please confirm.

Comment [M59]: Please add the volume and page number, or doi.

Comment [M60]: We added journal volume, please confirm.

Comment [M61]: We revised "1-12" "695-706", please confirm.

- | ~~29-27.~~ Santolin, A.; Cavazzini, G.; Pavesi, G.; Ardizzon, G.; Rossetti, A. Techno-economical method for the capacity sizing of a small hydropower plant. *Energy Convers. Manag.* **2011**, *52*, 2533–2541.
- | ~~30-28.~~ Cavazzini, G.; Santolin, A.; Pavesi, G.; Ardizzon, G. Accurate estimation model for small and micro hydropower plants costs in hybrid energy systems modelling. *Energy* **2016**, *103*, 746–757.

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.

Letter of Acceptance

The screenshot shows a Gmail interface with a browser window at the top. The browser tabs include 'INSPIRE Portal', 'Presensi - ENERGI BARU DAN TERB...', and '[Sustainability] Manuscript ID: - X'. The address bar shows the URL 'https://mail.google.com/mail/u/0/#inbox/FMfcgzGtxKXMNqVBkZzFmZJhzDxnKbrQ'. The Gmail interface features a left sidebar with navigation options like 'Tulis', 'Kotak Masuk' (5,012), 'Berbintang', 'Ditunda', 'Terkirim', 'Draf' (35), and 'Selengkapnya'. The main content area displays an email from 'Sustainability Editorial Office' with the subject '[Sustainability] Manuscript ID: sustainability-2606859 - Accepted for Publication'. The email body contains a congratulatory message and details about the manuscript acceptance.

[Sustainability] Manuscript ID: sustainability-2606859 - Accepted for Publication

Eksternal Kotak Masuk x

Sustainability Editorial Office <sustainability@mdpi.com> Sen, 25 Sep, 13.11 (20 jam yang lalu) ☆ ↶ ⋮

kepada saya, Rilya, Sustainability, Tundana

Inggris > Indonesia Terjemahkan pesan Nonaktifkan untuk: Inggris x

Dear Dr. Rumbayan,

Congratulations on the acceptance of your manuscript, and thank you for submitting your work to Sustainability:

Manuscript ID: sustainability-2606859
Type of manuscript: Article
Title: Feasibility Study of Micro Hydro Power Plant for Rural Electrification in Lalumpe Village, North Sulawesi, Indonesia
Authors: Meita Rumbayan *, Rilya Rumbayan
Received: 28 Aug 2023
E-mails: meitarumbayan@unsrat.ac.id, rilya.rumbayan@gmail.com

https://susy.mdpi.com/user/manuscripts/review_info/5d7f805dd78b3dbf5b99a30c3a8fc9c2

99+

Tulis

Mail

Kotak Masuk 6.528

Chat

Berbintang

Ditunda

Meet

Terkirim

Draf 44

Selengkapnya

Label

bahman.kermanshahi@g...



Sustainability Editorial Office <sustainability@mdpi.com>
kepada saya, Rilya, Sustainability

14 Sep 2023, 15.51

[Terjemahkan ke Indonesia](#) ✕

Dear Dr. Rumbayan,

Thank you again for your manuscript submission:

Manuscript ID: sustainability-2606859
Type of manuscript: Article
Title: Feasibility Study of Micro Hydro Power Plant for Rural Electrification in Lalumpe Village, North Sulawesi, Indonesia
Authors: Meita Rumbayan *, Rilya Rumbayan
Received: 28 Aug 2023
E-mails: meitarumbayan@unsrat.ac.id, rilya.rumbayan@gmail.com

Your manuscript has now been reviewed by experts in the field. Please find your manuscript with the referee reports at this link:

<https://susy.mdpi.com/user/manuscripts/resubmit/5d7f805dd78b3dbf5b99a30c3a8fc9c2>

Please revise the manuscript according to the referees' comments and upload the revised file within 10 days.

Please use the version of your manuscript found at the above link for your

99+

Tulis



Mail

Kotak Masuk 6.528

Chat

Berbintang

Meet

Ditunda

Terkirim

Draf 44

Selengkapnya

Label

bahman.kermanshahi@g...

[Sustainability] Manuscript ID: sustainability-2606859 - Revised Version Received

Eksternal Kotak Masuk ✕



Sustainability Editorial Office <sustainability@mdpi.com>

Min, 17 Sep 2023, 18:10

kepada saya, Rilya, Sustainability



Terjemahkan ke Indonesia



Dear Dr. Rumbayan,

Thank you very much for providing the revised version of your paper:

Manuscript ID: sustainability-2606859

Type of manuscript: Article

Title: Feasibility Study of Micro Hydro Power Plant for Rural Electrification in Lalumpe Village, North Sulawesi, Indonesia

Authors: Meita Rumbayan *, Rilya Rumbayan

Received: 28 Aug 2023

E-mails: meitarumbayan@unsrat.ac.id, rilya.rumbayan@gmail.com

https://susy.mdpi.com/user/manuscripts/review_info/5d7f805dd78b3dbf5b99a30c3a8fc9c2

We will continue processing your paper and will keep you informed about the status of your submission.